Skirt

IP44 RoHS

H x W (mm)	Profile	Ref.	Trunkings Characteristics				Insulated Cables Capacity				
			Internal Dim.	Length	Internal Section (S)	Available Section (Su)	Max ø Available	Max. Nr. Conductors H07 V-U			
			(mm)	(m)	(mm²)	(S/1,4) (mm²)	(mm)	1,5 mm²	2,5 mm²	4 mm²	6 mm²
110 x 2		10100 CBR	104x17	2,00	1 330 2 420 3 436	236 301 312	14 16 17	30 38 40	20 26 27	16 21 21	12 15 16

CBR - Complete White.

Floor

IP44 RoHS

W x H (mm)	Profile	Ref.	Trunkings Characteristics				Insulated Cables Capacity				
			Internal Dim.	Length	Internal Section (S)	Available Section (Su)	Max ø Available	Max. Nr. Conductors H07 V-U			
			(mm)	(m)	(mm²)	(S/1,4) (mm²)	(mm)	1,5 mm²	2,5 mm²	4 mm²	6 mm²
50 x 12		10110 CCZ	30x9	2,00	1 47 2 148 3 47	34 106 34	6 9 6	4 13 4	3 9 3	2 7 2	1 5 1
75 x 17		10120 CCZ	60x14	2,00	1 198 2 238 3 198	142 170 142	11 14 11	18 21 18	12 14 12	10 11 10	7 8 7

CCZ - Complete Grey.